SDMS US EPA REGION V -1

SOME IMAGES WITHIN THIS DOCUMENT MAY BE ILLEGIBLE DUE TO BAD SOURCE DOCUMENTS.




4CA 0156866

ATTENTION (ENVIRONMENTAL INSURANCE LITIGATION MATERIALS)

DO NOT DESTROY OR REMOVE WITHOUT SPECIFIC AUTHORIZATION FROM THE LAW DEPARTMENT. CALL 314-694-6060 OR 314-694-6032 FOR ADDITIONAL INFORMATION.





ACA 0156857

91 10/03 10:24

2314343 6046515832 MMECO / BISTATE

ð 1





4303 BISTATE DRIVE # 57. LOUIS, MISSOURI 83 129 314-497-7100 # 1-800-325-3322 # FX. 314-497-0883

EASCIMILE COVER SHEET

TO: HLANFAUST	DATE 10/3/91
MONSANTO CHEMICAL	PAGE / OF /
ATTN:	
BENDER: KICH SAHRMAN	
MESSAGE: RK: PROJECT WE DISCA FOLLOWING FIRM'S CAN DO TYPE W	
HELMKAMP CONST, WOOD RIVER: BYROW	
BARTON CONTRACTORS, SO, ROYMAN : JERRY	ERNO 618/254-7495
DIET WEEKS, HIGHLAND: LEE BUTTS	## 800/FS1. FL79



GARDNER-DENVER FATALLES.



MCA -150868

CONTENTS

			<u>Page</u>
1.0	INTI	RODUCTION	1
	1.1	SCOPE OF WORK	1
	1.2	SITE BACKGROUND	2
•		1.2.1 Site Location and Description 1.2.2 Site History 1.2.3 Previous Investigations	· 3
2.0	PHY	YSICAL CHARACTERISTICS OF THE STUDY AREA	6
	2.1	LAND USE	6
	2.2	TOPOGRAPHY AND DRAINAGE	6
	2.3	CLIMATE	7
	2.4	REGIONAL AND SITE GEOLOGY	7
3.0	INV	ESTIGATION FIELD ACTIVITIES	8
	3.1	SECTOR & BORING PROGRAM	8
	3.2	SITE L BORING PROGRAM	10
	3.3	SITE M BORING PROGRAM	10
	3,4	PHASE II INVESTIGATION	11
4.0	(PRO	DIECT ORGANIZATION AND SCHEDULING	11
5.0	REF	FERENCES	13

WCA -156869

TABLES

- 1. Summary of Volatile Organic Compounds Detected in Sediments and Soils from Dead Creek Sector B, and Sites L and M, Sauget Cahokia, Illinois.
- 2. Summary of Semivolatile Organic Compounds Detected in Sediments and Soils from Dead Creek Sector B, and Sites L and M, Sauget Cahokia, Illinois.
- 3. Summary of Pesticide and PCB Compounds Detected in Sediments and Soils from Dead Creek Sector B and Site M, Sauget Cahokia, Illinois.
- 4. Summary of Inorganic Compounds Detected in Sediments and Soils from Dead Creek Sector B, and Sites L and M, Sauget Cahokia, Illinois.

FIGURES

- 1. Location of Dead Creek Sector B, and Sites L and M, Sauget Cahokia, Illinois.
- 2. Location of Study Areas, Dead Creek Sector B, and Sites L and M, Sauget Cahokia, Illinois.
- 3. Schematic Diagram of Proposed Soil Boring Locations at Dead Creek Sector B, Sauget Cahokia, Illinois.
- 4. Sediment Sampling Locations at Site L, Sauget, Illinois.
- 5. Sediment Sampling Locations at Site M, Cahokia, Illinois.
- 6. Project Organization.
- 7. Project Schedule of Activities for the Soil Boring Program, Sauget Cahokia, Illinois.

APPENDICES

- A. Field Sampling Plan.
- B. Quality Assurance Project Plan.
- C. Health and Safety Plan.



WORK PLAN FOR A SITE INVESTIGATION FOR DEAD CREEK SECTOR B AND SITES L AND M, SAUGET-CAHOKIA, ILLINOIS

August 15, 1991

Geraghty & Miller, Inc. is submitting this Work Plan to Monsanto Company for a proposed site investigation at the Dead Creek Sites. The Work Plan was prepared in conformance with Geraghty & Miller's strict quality assurance/quality control procedures to ensure that the report meets the highest standards in terms of methods used and the information presented. If you have any questions or comments concerning this Work Plan, please contact one of the individuals listed below.

Respectfully submitted,

GERACHTY & MILLER, INC.

DRAFI

Ann Newton Staff Scientist

DRAFI

Brian Blum Senior Scientist/Project Manager

DRAFT

Dennis Colton
Project Director/Project Officer

MCA J156871

WORK PLAN FOR A SITE INVESTIGATION FOR DEAD CREEK SECTOR B AND SITES L AND M, SAUGET-CAHOKIA, ILLINOIS

1.0 INTRODUCTION

At the request of Monsanto Company, St. Louis, Missouri, Geraghty & Miller, Inc. has prepared this work plan for a site investigation at Dead Creek Sector B and Sites L and M, Sauget-Cahokia, Illinois. The purpose of the study is to characterize conditions at the sites by determining the nature and extent of sediment/fill materials that are present and estimate the volume of material affected by organic compounds and/or metals. Throughout this work plan, the site(s) will be referred to as Sector B, Site L and Site M, which were identified by the Illinois Environmental Protection Agency (IEPA) as Dead Creek Sector B, Sauget Site L, and Sauget Site M (Ecology & Environment [E&E], 1988). The study area is shown on Figures 1 and 2.

This work plan describes the scope of work associated with the sites investigations. Three project operation plans are provided as appendices. A field sampling plan (FSP), describing the sampling protocols, is presented in Appendix A. The quality assurance project plan (QAPP), providing procedures for assuring the quality of the analytical data, is contained in Appendix B. The health and safety plan (HASP) is provided in Appendix C and describes procedures to protect the health and safety of the investigation team.

1.1 SCOPE OF WORK

A field investigation will be conducted which will consist of a focused boring and sampling program. Specific testing locations and the recommended analyses at each of the three sites have been selected based upon historical information and previous investigations discussed in Sections 1.2.2 and 1.2.3. The field program will be conducted in two phases.

A boring program will be conducted to characterize sediment/fill material at each of the sites and to determine its areal extent. After the nature and extent of the sediment/fill at each of the sites has been defined, a second phase of sampling will be undertaken to classify materials, reactivity, ignitability, corrosivity, and toxicity using the Toxicity Characteristic Leaching Procedure (TCLP).

1.2 SITE BACKGROUND

A description of the site locations, site histories, and previous investigations is presented in the following sections.

1.2.1 Site Location and Description

Dead Creek Sector B, and Sites L and M are located in Sauget and Cahokia, St. Clair County, Illinois. The sites are located on the north-central part of the Cahokia, Illinois-Missouri U.S. Geological Survey (USGS) topographic quadrangle (Figure 1). Dead Creek Sector B is about 2000 feet in length and lies between Queeny Avenue to the north and Judith Lane to the south Sector B encompasses an area of about 230,000 square feet (ft²)(Figure 2). In general, the creek area consists of a narrow channel that is about 5 feet wide. Water levels in the creek vary, depending on precipitation and water table fluctuations. During periods of little precipitation and low water table, the creek becomes a dry ditch. The channel of the creek bed is flanked by a low bank on either side which may often be under water. The channel and the low banks are enclosed by steeper, heavily vegetated banks. Standing water cannot drain out of Sector B to other parts of Dead Creek because both the influent (north) and effluent (south) ends of Sector B have been sealed.

Sites L and M are located adjacent to Creek Sector B (Figure 2). Site L is located on the east side of Sector B and approximately 700 feet south of Queeny Avenue. Based on a figure in a report prepared by the IEPA (St. John, 1981), the site's (L) approximate dimensions are 70 feet by 150 feet. The subsequent study by an IEPA consultant (E&E.

1988) indicates the dimensions of Site L to be 70 feet by 150 feet. The figures depict a site with dimensions of about 195 feet by 145 feet. This discrepancy is likely due to the site boundaries drawn by E&E, which included a larger area than the actual impoundment basin. Therefore, for the purposes of this study, the site boundaries are assumed to be those depicted on the E&E (1988) report figures. Site L includes a portion of the property owned by Metro Construction Company. The site is covered with black cinders and construction vehicles are parked across the area. Access to the site is not restricted.

Site M is adjacent to the southeast part of Sector B and it is about 200 feet north of Judith Lane. The site is a former pit that was formed by sand mining. Presently, the pit is filled with water at least 2 feet deep. Site M is connected to Creek Sector B by a drainage way which allows water to flow from the creek to the pit. The dimensions of Site M are about 335 feet by 235 feet. Site M, along with all of Creek Sector B, is surrounded by a chain-link fence which was installed by the U.S. Environmental Protection Agency (USEPA) to restrict access.

1.2.2 Site History

Formally, Dead Creek provided drainage for part of the Mississippi floodplain and water in the creek flowed in a southwesterly course to the Prairie Dupont Floodway which ultimately discharged to the Cahokia Chute of the Mississippi River. However, Dead Creek, particularly Sector A (immediately north of Sector B) and Sector B have been a concern since the early 1970s when area residents filed complaints with the Cahokia Health Department regarding discharges to the creek (Ecology & Environment, 1988). As a result of these concerns, culverts on the north and south ends of the Sector B portion of the creek were sealed to prevent surface water from flowing freely into or out of that part of the creek. Additionally, the creek may have been affected by former pits or excavations (e.g., Sites L and M) adjacent to its banks (St. John, 1981). Since that time, several federal and state agencies have conducted surveys, site inspections, and studies of Dead Creek and adjacent former pit/excavation areas.

MCA J156874

Site L was used as a disposal impoundment basin by Harrold Waggoner and Company, a trucking firm which operated at the site from 1964 to 1974. Discharges to the impoundment at Site L began after 1971, after Harrold Waggoner and Company was cited by the IEPA for discharges directly into Dead Creek within Sector B. Ruan Trucking Company also used the impoundment basin for disposal purposes after they purchased the operation in 1974. Disposal activity at site L ceased after 1978 when the property was sold to Metro Construction Company, the site's present owner (E&E, 1988). The site is covered with cinders and serves as a depot for large construction machinery, along with adjacent areas.

Site M was a sand mining area excavated in the 1940s by H.H. Hall Construction Company. This area was mined prior to any residential development along Walnut Avenue, east of Site M. The E&E Report (1988) reported the owner of the property as Thomas Owen.

1.2.3 <u>Previous Investigations</u>

In 1980, the IEPA initiated an investigation of Dead Creek and adjacent areas as a result of complaints from local area residents. The IEPA study (St. John 1981) consisted of analyzing 31 soil samples (19 from Sector B) to determine the affect of disposal practices. Information from five hand auger and 12 drill rig boring locations was used to characterize local geologic conditions. In addition, surface water samples and ground-water samples were collected and analyzed. The study concluded that sediment samples collected from Dead Creek contained polychlorinated biphenyls (PCBs), organic compounds and metals. The report also concluded that ground water and surface water were also affected by organic and inorganic constituents.

In 1986, E&E initiated a remedial investigation (RI) on behalf of the IEPA at several sites in the Sauget area, which included Sector B and Sites L and M. In Sector B, E&E collected two surface water samples and five sediment samples from the north and south

MCA .31 56875

ends of site. A summary of the soil and sediment analytical data collected by E&E is provided in Tables 1 through 4.

Four borings were used by E&E (1988) to characterize conditions at Site L. Data from the borings indicate that the impoundment basin was excavated approximately eight feet into a deposit chiefly composed of sand with silt. The excavation was filled with material consisting of black cinders, clay and concrete. The contact between till material and the underlying sand and silt deposits are believed to be an indication of the impoundment basin's extent. E&E reported that past disposal activities have affected sediment and ground-water quality. Constituents detected include benzene, toldehe, phenols, and arsenic. PCBs were not detected.

In 1986, E&E collected two surface water and five sediment samples in the excavated area of Site M. The results from these samples indicate that the site sediments have been impacted by past disposal activities. However, it is not clear whether or not Site M was a disposal area or was affected by surface water drainage from Dead Creek. Surface water samples did not exhibit constituent concentrations indicative of disposal impacts.

The Advendt Group, Inc. sompleted a site investigation/remedial alternatives evaluation for Creek Sector A (1990) which is located north of Sector B on property owned by Cerro Copper Products Co. The Advendt Group study consisted of a field program initiated in July 1989 to characterize and define the constituents in Creek Sector A and determine the volume of sediments requiring remedial action. Ninety nine sediment samples were collected from 34 soil borings along ten transects of Sector A. The report concluded that fill and creek channel sediments ranged in thickness from one to 15 feet and a half foot to 11 feet, respectively. These materials contained concentrations of organic compounds including PCBs as well as inorganic analytes (metals). It was estimated that approximately 19,500 cubic yards of creek bottom sediments was affected by chemical constituents.

MCA J156876

2.0 PHYSICAL CHARACTERISTICS OF THE STUDY AREA

This section describes the physical setting of the sites. Discussed below are land use, topography and drainage, climate, and geology.

2.1 LAND USE

The Sauget area (north of the study area) is heavily industrialized. More than half of the land use in the town of Sauget is industrial. The Sauget area is within a major transportation corridor provided by the Mississippi River, numerous interstate highways, and a large railroad center. A number of industrial properties are north of Sector B and they include Cerro Copper Products Co., Monsanto Company, Big River Zinc, Midwest Rubber Company, Mobil Oil Company, and Sterling Steel Foundry. Land use in Cahokia (southern part of the study area) is residential, commercial and agricultural. Immediately adjacent to the central and southern portions of Sector B are cultivated fields. Site M is adjacent to a small residential area off of Walnut Street and Judith Lane.

2.2 TOPOGRAPHY AND PRAINAGE

The study area is located on the flood plain of the Mississippi River and is within the physiographic region known as the American Bottoms. Generally, the flood plain's land surface lies between elevations of 400 and 445 feet above National Geodetic Vertical Datum (NGVD) and locally, the sites are about 405 feet above NGVD. The topography of the area is predominantly flat with the exception of the steep bank of Dead Creek. Surface runoff from the area flows toward Dead Creek - Sector B, which ultimately drains into Site M.

MCA 0156877

6

2.3 CLIMATE

The climate of the site(s) area is continental with hot, humid summers and mild winters. Periods of extreme cold are of short duration. The average annual rainfall in the area for the period from 1903 to 1983 was 35.4 inches; however, precipitation increased to 39.5 inches per year during the period from 1963 to 1988 (Southwestern Illinois Metropolitan and Regional Planning Commission (1983). The average annual temperature is 56°F; the highest average monthly temperature (79°F) occurs in July and the lowest average monthly temperature (32°F) occurs in January.

2.4 REGIONAL AND SITE GEOLOGY

The site(s) is situated on the flood plain of the Mississippi River (Figure 1). The flood plain is locally named the American Bottoms, and contains unconsolidated valley fill deposits composed of recent alluvium (Cahoka Alluvium) which overlies glacial material (Henry Formation). Published information indicates that these unconsolidated deposits are underlain by bedrock of Pennsylvanian and Mississippian age which consists of limestone and dolomite with lesser amounts of sandstone and shale.

The Cahokia Alluvium (resent deposits) consists of unconsolidated, poorly sorted, fine-grained materials with some local sand and clay lenses. These recent alluvium deposits unconformably overlie the Henry Formation which is Wisconsinian glacial outwash in the form of valley-train deposits. The Henry Formation is about 100 feet thick. These valley-train materials are generally medium to coarse sand and gravel and increase in grain size with depth.

During the various drilling programs conducted on-site, the alluvium underlying Dead Creek has been characterized as a silt with local clay and sand lenses (St John 1981). The deposits tend to become coarser with depth. The Advendt Group (1990) categorized the stratigraphy in Sector A as being comprised of the four following units in descending order:

MCA 156978

7

fill material, fluidized creek bottom sediments, Cahokia Formation, and Henry Formation. The fill material is composed of sand and silt matrix intermixed with concrete, bricks, road aggregate, rags, slag, and vitreous pellets. The fluidized creek bottom sediments are saturated silts with organic matter. The Cakohia and Henry formations have been described similar to that discussed above.

3.0 INVESTIGATION FIELD ACTIVITIES

A boring program will be conducted to characterize the sediment/fill at each of the sites. Described below are the different sampling strategies and rationales for Sector B, and Sites L and M. After the boring programs discussed below are complete, a phase II program will be initiated to classify the material.

Access to Sector B and Site M will be gained through lockable gates that will be installed at four locations. Gate locations will be chosen to facilitate movement into and out of the sites which is hindered by steep banks within Sector B and Site M. Gravel fill will be brought onto the site to aid in the construction of access ramps. Land clearing of small trees and underbrush will be required to move within Sector B.

3.1 SECTOR B BORING PROGRAM

Sediment/fill samples will be collected along ten profiles (transects) within the creek bed, spaced approximately 200 feet apart, throughout the 2,000-foot length of Sector B. As shown on Figure 3, three borings are proposed for each profile similar to the study conducted in Sector A (Advendt Group 1990). All borings will be drilled to determine the thickness of the sediment/fill in the creek and will be spaced, within a given transect, 15 to 20 feet apart. The limits of the creek bottom sediments/fill will be determined visually by a field geologist during the drilling operations. It is anticipated that the borings within the creek bed will be drilled to a maximum depth of about 7 feet. Samples will be collected using a 5-foot continuous tube sampler, and 3-inch diameter split spoons will be used if

MCA ,156879

recovery is poor in the fine sandy sediments. Both methods will provide a continuous record of the geology, as well as a sufficient volume of material for analysis. All samples will be described by the Geraghty & Miller field geologist who will record sample location, depth, grain size distribution, and color. Each sample will also be screened in the field for the presence of volatile organic compounds (VOCs) using a photoionization detection (PID) instrument.

Based on appearance and PID measurements, we propose to select one sediment/fill sample per borehole for chemical analysis. Each sample will be selected from a 2-foot interval that best characterizes sediment/fill in the creek. One sediment/fill sample per transient will be analyzed for the USEPA target compound list/ target analyte list (TCL/TAL) parameters. The remainder of the samples from the transect will be analyzed for TAL parameters (metals) and PCBs. Appropriate quality assurance/quality control (QA/QC) samples will also be collected. The analytical data from the sediment/fill will be used to delineate any impacted areas, as well as provide an estimate of the volume of sediment/fill present. Each borehole will be sealed with a mixture of drill cuttings and bentonite grout and the borehole's location and land surface elevation will be surveyed by a licensed land surveyor. All drilling equipment will be steam cleaned after each borehole and all sampling equipment will be decontaminated with a laboratory-grade detergent and potable water before the collection of each sample.

At present, we propose to use an all-terrain vehicle (ATV) drill rig for the entire program. However, in some areas, it may be necessary to pump off standing water to provide suitable sampling conditions. If there is a great deal of standing water, and it is not feasible to pump it off to another part of the creek, the drill rig can be mounted on a reinforced aluminum pontoon that can be anchored to the creek channel bank with steel cables. This drilling method was used in Creek Sector A by Advendt Group (1990).

3.2 SITE L BORING PROGRAM

To define the lateral and vertical extent of the fill material at Site L, additional borings are required to supplement the data collected previously (E&E 1988). Since this site is relatively small (70 feet by 150 feet), only six borings are necessary to categorize the nature and extent of the fill material. These borings will be drilled at strategic locations to supplement the existing borings drilled during the E&E investigation (1988) (Figure 4).

At each boring location, we propose to collect continuous samples, using a 5-foot tube sampler or a 3-inch diameter split-spoon, to delineate the bottom of the fill. Five borings will be drilled at the perimeter of the former impoundment (as identified by E&E) to determine its actual boundaries. A visual examination by the field peologist will be used to determine whether or not the boring is within the former impoundment basin. If necessary, boring locations will be adjusted to ascertain the former impoundment basin boundaries and characterize the fill material. The remaining boring will be drilled near the center of Site L to determine maximum fill thickness. One sample per borehole (six boreholes) will be submitted for laboratory analysis. The sample that best characterizes the fill material will be selected for analysis. The criteria for sample selection will be visual indicators such as discoloration and high PID readings. Each sample will be limited to a 2-foot section of the continuous core. At two of the six borings, the samples will be analyzed for PCBs, TAL metals, and TCL VOCs. Each borehole will be sealed and surveyed as described for Dead Creek - Sector B.

3.3 SITE M BORING PROGRAM

At Site M, sediment samples will be collected from three locations from beneath the ponded water (Figure 5). To obtain the samples, a soil boring drill rig supported by the aluminum pontoon previously described in Section 3.1 may be used, or samples may be collected from a boat. This method of supporting a drill rig on surface water has been used

successfully at other sites (Advendt Group, Inc. 1990). If the samples are collected from a boat, 4-inch diameter steel casing will be driven into the pond sediments and split-spoon samples will be obtained from within the casing to determine the thickness of the sediments. One sample for laboratory analysis will be selected from each of the three locations at the 0 to 2-foot interval. At one location, the sample will be analyzed for TCL/TAL parameters, and at the other two locations, each sample will be analyzed for PCBs and TAL metals. We have assumed that the pit bottom is at a maximum depth of 10 feet below the pond level. Sample selection protocols and decontamination procedures will be the same as was described for Dead Creek - Sector B.


3.4 PHASE II INVESTIGATION

Once the chemical nature of the sediment/fill material has been determined, approximately five samples will be collected during a second phase of field work to classify the material. Each of these samples will be analyzed for reactivity, corrosivity, ignitability, and toxicity using the TCLP.

4.0 PROJECT ORGANIZATION AND SCHEDULING

All field activities will be conducted in accordance with specific field, analytical, and health and safety protocols outlined in the FSP (Appendix A), the QAPP (Appendix B), and the HASP (Appendix C), respectively. Primary responsibility for the study will be shared by the Geraghty & Miller project officer and project manager (see Figure 6). They will be responsible for the scheduling and coordination of all Geraghty & Miller personnel on the project and for providing technical assistance for all activities which are directly related to the study. The Geraghty & Miller QA/QC advisor will have the responsibility for all QA/QC review to ensure that work is performed in accordance with established protocols.

The schedule for the sites investigation and evaluation is shown on Figure 7. The investigation will begin upon notice of approval of this work plan and authorization to proceed from Monsanto Company. A 30-week schedule is shown for performance of tasks and development/submittal of preliminary and final reports.



MCA J156883

5.0 <u>REFERENCES</u>


- Advent Group, Inc. 1990. Site Investigation/Remedial Alternatives Evaluation for Creek Segment A. June 1990.
- American Conference of Governmental Industrial Hygienist, Threshold Limit Values. 1990-1991.
- Ecology and Environment, Inc. 1988. Expanded Site Investigations Dead Creek Project Sites at Cahokia/Sauget, Illinois, Final Report. May 1988.
- National Institute of Occupational Safety & Health. Occupational Health Guides. 1978-1989.
- Occupational Safety & Health Administration. U.S. Department of Labor, General Industry Health & Health Standards. 1970-1989.
- St. John, Ron. 1981. A Preliminary Hydrogeologic Investigation in the Northern Portion of Dead Creek and Vicinity. April 1981.
- U.S. Environmental Protection Agency (USEPA) 1980. Interim Guidelines and Specifications for Preparing Quality Assurance Project Plans. QAMS-005/80.
- U.S. Environmental Protection Agency (USEPA). 1986. Test Methods for Evaluating Solid Waste Physical/Chemical Methods SW-846. September 1986.
- U.S. Environmental Protection Agency (USEPA). 1988. Laboratory Data Validation Functional Guidelines for Evaluating Organic Analyses. February 1988.
- U.S. Environmental Protection Agency (USEPA). 1988. Contract Laboratory Program Statement of Work for Organics Analysis. February 1988.
- U.S. Environmental Protection Agency (USEPA). 1988. Laboratory Data Validation Functional Guidelines for Evaluating Inorganic Analyses. July 1988.
- U.S. Environmental Protection Agency (USEPA). 1990a. Contract Laboratory Program Statement of Work for Inorganic Analysis. OLM01.0.
- U.S. Environmental Protection Agency (USEPA). 1991. Region V Model Superfund Quality Assurance Project Plan (QAPiP). May 1991.

MCA U156884



EPA/CEPRO COPPER/EIL/PCB ATTORNEY WORK PRODUCT / ATTORNEY CLIENT PRIVILEGE

				Sector B		
						\
	Sample Identification:	DC-L1-02	DC-SD-14	DC-SD-18	DC \$D-19	PC-SD-20
	Sample Depth:	(0-0.5")	(2-3')	(0-0.5')	(0-0:5')	(1.5-2')
.	Sample Date:	11/5/86	11/5/86	11/5/86	11/5/86	11/5/86
Paramet	•••			/	\wedge	
concen	trations in ppb)	,		/- -	/	
Methyle	ne chloride	11000 B	2200	12900	/) 13000	14000
Acetone		15000 B	820	4180	/ 10000	6100
Chlorok	orm	-	~	-\	-	-
2-Butan	one (MEK)	21000 B	510	14000	14000	10000
Benzeni	•	-	87	-	-	
	1-2-pentanone	-	220	<u>.</u>		
2-Hexan		-	-/		52000	
Toluene		-	810	· , · · · · · · · · · · · · · · · · · ·	~	**
Chlorab			5200			
Ethylbe			3600\ 990	/ ~ -	-	-
Total Xy	107105	-			-	
Saaa	of data - Ecology & Environment (1988).			7		
Source	о одш Есоноду в Енчионители (1906).					
8	Compound detected in blank samples.		, <u>L</u>			
J	Estimated value. Result is less than the s	pecified detection limi	it, but greater than zer	0 .		
-	Not detected.	/ //	<u> </u>			
NA	Not analyzed.	\ \	\langle			
ppb	Parts per billion.		>			



MCA 3156887




Table 2. Summary of Semivolatile Organic Compounds Detected in Sediments and Soils from Dead Creek Sector B, and Sites L and M. Sauget - Cahokia, Illinois.

			Sector B-		
Sample Identification:	DC-SD-13	DC-SD-14	DC-SD-18	DC-SD-19	DC-SD-20
Sample Depth:	(0-0.5')	(2-3")	(0-0:5')	(0-0 5')	(1 5-2')
Sample Date:	11/5/86	11/5/86	11/5/86	11/5/86	11/5/86
Parameter				^	
concentrations in ppb)				/	
Icenaphthene	-	-	_	/ <	-
l-Nitrophenol	-	2600 J	-	/ ^ - \	-
Diethylphthalate	_	-		\/\-\	-
Pourene	-	3900 J	-	· / /	-
texachiorobenzene	_	-	-	1900	210
Pentachiorophenol	_	-	\wedge	940 J	370
Phenanthrene	•	15000 J	/ >	-	-
Di-n-butyl phthalate	-	-	200 /3	•	280
Juoranthene	-	11000 J	/ -	-	••
yrene	_	13000 J	1400,4	-	91
Sutyl Benzyl phthalate	-	-	\ 830 \	-	-
lenzo (a) Anthracene	-	-	430 1	-	_
is(2-Ethylhexyl) phthalate	9900 J	9500 J	\$300	_	95
thrysene	-		1200 J	-	180
oi-n-octyl phthalate	-	2000 J	940 J	-	96
lenzo (b) fluoranthene	-	3400 J		2400	-
Senzo (k) fluoranthene	720 J	1 5-	1500 J	-	410
lenzo (a) pyrene	1100 J	\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	/ 490 J	310 J	95
dena (1,2,3-cd)perylene	-	\	ັ 850 J	1400 J	200
Dibenz (a,h) anthracene	-	\	-	390 J	_
Phenoi	-	\	1400 J	1800 J	210
-Chiorophenoi	<u> </u>	\ /-	•	-	-
,4-Dichlorobenzene	/ \-	220000	-	-	-
,2-Dichlorobenzene	/)-	17000 J	-	130 J	-
-Methylphenol	\wedge	-	-	-	-
litrobenzene	\\\\ ->	•	-	-	-
.2,4-Trichlorobenzene	\\ -/	5400 J	-	390 J	76
lapthalene	, 100 1	9500 J	190 J	120 J	_
-Methylnapthalene	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	8400 J	_	_	_

Source of data - Esology & Environment (1988).

В

Not detected.

ppb Parts per billion

MCA 9156889

SEMIDEAD.XLS

GERAGHTY & MILLER, INC.

Compound detected in blank samples. Estimated value. Pesuit is less than the rsult ja less than the specified detection limit, but greater than zero.

Table 2. Summary of Semivolatile Organic Compounds Detected in Sediments and Soils from Dead Creek Sector B. and Sites L and M, Sauget - Cahokia, Illinois.

				Site L		
Sampl	e Identification: Sample Depth: Sample Date:	DC-L1-02 (5-10') 12/12/86	DC-L2-03 (5-15') 12/12/86	DC-L3-04 (5-15') 12/12/86	OC-L4-09 (10-20') 12/17/86	DC-L4-10 (10-20') 12/17/86
Parameter					\wedge	
concentrations in ppb)					/	
cenaphthene		_	-	-	/ <	_
I-Nitrophenal		-	44 J	-	/ \	
Diethylphthalate		-	-	-	(/ - \	310
Flourene		_	-	-	· / /	-
Hexachlorobenzene		_	-	_	-\ /	-
Pentachiorophenol		-	11538	58224	_ ~	_
Phenanthrene		-	602	1772 3	_	_
Di-n-butyr phthalate		171 J	372 J	2764	_	_
Tuoranthene		_	448	/ (/-)	-	_
yrene		-	282 J	-/	_	-
Butyl Benzyl phthalate		-	-	\ -(_	-
Benzo (a) Anthracene		-	_	911 J	_	-
ois(2-Ethylhexyl) phthalati	•	-	1217	\- /	750	1297
Chrysene		-	205 J	\searrow	-	-
Di-n-octyl phthalate		_		-	-	-
Benzo (b) fluoranthene		-	/>		_	-
Benzo (k) fluoranthene		-	1 5-	> -	-	-
Benzo (a) pyrene		-	\ V-~	_	-	
dena (1,2,3-cd)perylene		••	\	~ -	-	-
Dibenz (a,h) anthracene		-	\ (-	-	-	-
Phenol		-	\ 34¢6 J	1519 J	-	-
2-Chiorophenoi		<u> </u>	\ /-	2152	-	-
.4-Dichtorobenzene	,	/ \-	V -	215 J	-	-
.2-Dichlorobenzene		_ }-	-	-	-	-
-Methylphenol		\wedge	. 88 J	1089 J	-	-
Nitrobenzene	('	\〈 -〉	-	-	-	49
1,2,4-Trichlorobenzene		\\ -/	-	-	-	-
Napthalene		/ >	154 J	532 J	-	-
2-Methylnapthalene	\	\ > -	333 J	1000 J	-	-

Source of data - Epology & Environment (1988).

B Compound detected in blank samples

- Not detected.

NA Not analyzed.

ppb Parts per billion

MCA J15689J

J Estimated value. Result is less than the specified detection limit, but greater than zero.

Table 2. Summary of Semivolatile Organic Compounds Detected in Sediments and Soils from Dead Creek Sector 8, and Sites L and M, Sauget - Cahokia, Illinois.

			Site M-		
Sa	imple Identification: Sample Depth: Sample Date:	DC-SD-15 (0-0.5') 11/5/86	DC-SD-16 (0-0.5') 11/5/86	DC-SD-17 (0-0.5') 11/5/86	
Parameter	•	. ,	, ,		^
concentrations in ppt	o)			· · · · · · · · · · · · · · · · · · ·	\longrightarrow
cenaphthene			_	_	
I-Nitrophenol		-	-	-	
Diethylphthalate		_	_	-	
Plourene		-	_	-	` \
dexachiorobenzene		- '	-	-	
Pentachiorophenol		-	-	\wedge	V
Phenanthrene		-	-	/ >	
i-n-butyl phthalate		580 B	570 BJ	****	\
luoranthene			-	/ 💯	>
yrene		-	-	\ '-/	,
Butyl Benzyl phthalate	,	_		/ - (
Benzo (a) Anthracene		-	-	\ - `	
is(2-Ethylhexyl) phth		-	540 J	J20 T	/
hrysene		-			
Di-n-octyl phthalate		120 J	270.	_	
Senzo (b) fluoranthen	•		/		
Benzo (k) fluoranthen		_	1 /-	> -	
Benzo (a) pyrene		-	\ V-~	/ -	
deno (1.2,3-cd)peryle	ne	-	\ \ \	~	
Dibenz (a,h) anthracer		_	\	-	
Phenol		-	/ /	_	
2-Chlorophenol		<u> </u>	\ /-	-	
.4-Dichlorobenzene		/ \ -	V _	-	
.2-Dichtorobenzene		` <u>}</u> _	•	_	
-Methylphenol		\wedge	_	-	
litrobenzene		$\langle \rangle >$		-	
.2.4-Trichlorobenzeni	•	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	_	_	
Napthalene	`		_	_	
2-Methylnapthalene	\	\ \ \	_	_	

Source of data - Esology & Environment (1988).

В

Compound detected in blank samples.
Estimated value. Result is less than the specified detection limit, but greater than zero. J

Not detected.

NA Not analyzed.

Parts per billion ppb

MC4 J156891

ACA F

J156892

EPA/CERRO COPPER/EIL/PCB ATTORNEY WORK PRODUCT / ATTORNEY CLIENT PRIVILEGE

Table 3. Summary of Pesticide and PCB Compounds Detected in Sediments and Soils from Dead Creek Sector B and Site M, Sauget - Cahokia, Illinois Sample Identification: DC-SD-15 DC-SD-16 DC-SD-17 (0-0.5)Sample Depth: (0-0.5)(0-0.5)11/5/86 Sample Date: 11/5/86 11/5/86 Parameter (concentrations in ppb) 20000 Aroclor-1242 8830 5200 Aroclor-1248 660 Aroclor-1254 670 4200 2700 J Aroctor-1260 430 J PCBs (Total) Source of data - Ecology & Environment (1988). С Result confirmed by GC/MS. Estimated value. Result is less than the specified detection limit, but greater than zero. Not detected. NA Not analyzed. Parts per billion. ppb

_156893

Page 1 of 3

Sample Identification: DC-SD-13 DC-SD-14 DC-SD-16 DC-SD-76 Sample Date: 11/5/66 11/5/6	Sample Depth: (0.05) (2.05) (0	Sample Depth: DC-SD-13 DC-SD-14 DC-SD-16 DC-SD-76 DC-S	Sample Death: DCSD-13 DCSD-14 DCSD-16 DCSD-16 DCSD-16 DCSD-16 DOSJ DGSS DGSS DGSS DGSS DGSS DGSS DGSS DG				Sector B		
Sample Depth: (00.5) (2.3) (00.5) (00.5) (00.5) (1/5/86 11/5/8	Sample Dayst: (0.0.5) (2.3) (0.0.5) (1.5/86 11/5/86 11	Sample Days: 11/5/86 1	Sample Date: 11/5/86 1	Samole Identification:	DC-SD-13	DC-SD-14	DC-SD-18	oc so re	BC-SD-20
4600 6360 5380 12 14 R 20 R 16 R 21 410 1110 467 17300 12 410 1110 467 17300 12 410 1110 467 17300 12 6.6 8.2 24 30 6.2 153 79 118 6.6 8.20 118 6.6 8.20 118 6.6 8.20 118 6.7 1130 111 6.7 118 6.8 8.2 15300 8200 21 197 113 2.18 82 198 4.1 4 4 2 20 27 28 82 1530 R 28 21 20 R 4.1 4 48 22 27 28 44 48 23 310 6650 3410 11900	4600 6380 5380 12 14 R 20 R 16 R 15 R 17300 13 22 36 24 30 22 36 82 R 6 11 6.6 6.7 17300 118 6.6 6.7 17300 118 6.6 6.7 17300 118 6.7 133	4600 6380 5380 12 14 R 20 R 16 R 21 410 1110 467 17300 3 62 133 79 118 6.6 870 860 118 6.6 870 860 118 6.6 800 118 6.7 82 82 6.8 860 118 6.8 8200 21 197 113 0.9 188 19 8 Environment (1988). 19 8 Environment (1988). 10 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	4800 6380 5380 12 14 R 20 R 16 R 21 410 1110 467 17300 3 62 133 79 118 6.6 82 21 79 118 82 24 80 118 82 24 80 118 82 24 80 118 82 24 80 118 82 24 80 118 82 24 80 118 82 128 80 118 82 128 80 118 82 128 80 118 82 128 80 118 82 128 80 118 128	Sample Depth:	(0-0-5')	(2-3') 11/5/86	(0-0.5°) 11/5/ 86	11/5/86	7.5-2') 11/9/86
4000 6300 5300 12 14 R 20 R 16 R 21 410 1110 467 17300 22 36 24 30 62 153 79 118 6.6 92 6 11 6.6 92 6 11 6.7 0 6700 15500 21 1.1 110 640 1.2 110 640 1.2 110 640 1.3 0.9 168 2.3 1.3 0.9 168 2.4 3.3 4.1 118 1.4 15 2.5 2.5 2.6 2.7 118 2.7 2.4 3.3 1.3 1.3 1.3 1.4 1.5 2.7 2.4 3.3 1.3 1.3 1.3 1.4 1.5 2.7 2.4 4.1 1.5 2.8 8 R 50 R 60	4900 6390 5390 12 14 R 20 R 16 R 21 410 1110 467 17300 22 36 24 30 22 36 8-2 24 30 25 36 8-2 26 8-2 15 19 119 16 40 1500 16 40 1500 27 13 0 9750 12 28 24 30 29 118 85 30 640 10 119 10 119 11 14 15 12 22 28 33 4 4.1 11 14 15 12 22 28 33 10 11900 68 30 310 11900	4600 6380 5380 12 14 R 20 R 16 R 21 410 1110 467 17300 3 22 36 R 24 30 62 133 79 118 62 130 8640 118 64.40 6700 16600 2 65.5	4600 6380 5380 12 14 R 20 R 16 R 16 R 17300 310 22 36 24 30 24 30 25 36 24 30 26 28 92 66 6 111 6740 15300 21 68 92 68 660 1450 140 15300 21 150 150 150 150 150 150 150 150 15						
14 R 20 R 16 R 21	14 R 20 R 16 R 21	14 R 20 R 16 R 21 410 1110 467 21 22 36 24 30 22 36 24 30 22 36 24 30 11 6 8 21 22 36 24 30 11 6 8 21 11 6 8 21 11 6 8 21 11 10 16 8 21 11 10 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 110 11 10 1100 11 1	14 R 20 R 10 R 21 11	nnum	1900	0829	0985	05.76	12900
14 R 20 R 16 R 21	### 20 R 16 R 27	14 R	14 R	mony	;	ı	```	・: へ >	1 9
410 1110 467 17300 3 22 36 24 30 22 36 8.2 4 30 23 79 118 6.6 8.2 6 6 11 6.6 8.2 6 6 11 6.6 8.2 6 6 11 6.6 8.2 6 6 11 6.7 8.2 6 6 14.0 197 153 986 1.3 0.9 1.68 5.8 79 153 0.9 1.68 5.8 79 1.52 0.9 1.68 5.8 79 1.53 0.9 1.68 5.8 79 79 1.53 0.9 1.68 5.8 79 79 1.53 0.9 1.68 5.9 73 1.1 1.1 1.4 1.5 7.0 73 1.1 1.1 1.4 1.5 7.0 73 1.1 1.1 1.4 1.5 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 73 7.1 1.3 0.9 1.68 7.0 7.3 7.1 1.3 0.9 1.8 1.8 1.8 1.8 1.8 1.8 1.8 1.8 1.8 1.8	110	### 110 467 17300 3 3	Litivalent 410 1110 467 17300 3 22 36 24 30 22 133 79 118 87-40 18500 18500 21 18-40 18-5000 18500 18500 21 87-40 18-5000 18500 21 87-40 18-5000 21 8	nic	₹	8	9 9	2	H 65
22 36 24 30 24 30 25 153 79 118 6.6 9.2 6 6 111 6.6 0 9.2 6 6 111 6.6 0 9.2 6 6 111 6.6 0 9.2 6 6 111 6.6 0 9.2 6 6 111 6.6 0 9.2 1530 9 79 153 931 97 153 218 82 98 168 98 168 98 168 98 168 98 168 98 168 99 168 90 1189 90 1190 90 1190 90 1190	2 36 24 30 118 6.6 9.2 15.3 79 118 6.6 9.2 15.3 79 118 6.6 9.2 15.3 79 118 6.6 9.2 15.3 79 118 6.6 9.2 15.30 9.6 118 0.0 9.2 15.30 9.6 118 0.0 9.2 15.30 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.2 15.20 9.6 118 0.0 9.6 9.7 15.2 15.20 9.6 9.7 15.2 15.20 9.6 9.7 15.2 15.20 9.6 9.7 15.2 15.20 9.6 9.7 15.2 15.20 9.6 9.7 15.2 15.20 9.7 15.2 15.2 15.2 15.2 15.2 15.2 15.2 15.2	11	Litivalent 62 36 24 30 118 6.6 6.5 153 79 118 6.6 6.5 1530 82 119 119 119 119 119 119 119 119 119 11	E	410	1110	/ 194	17300	3120
22 36 24 30 86.6 9.2 79 118 8740 • 6700 6640 118 8750 • 15300 • 21 11 15300 • 21 11 15300 • 21 11 16500 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 16500 21 11 1660 21 1	22 36 24 30 118 118 119 11	22 36 24 30 118 118 119 118 119 119 119 119 119 119	22 36 24 30 118 119 119 119 119 119 119 119 119 119	Nium	1	:	1	·	ı
22 36 24 30 118 118 119 119 119 119 119 119 119 119	1, tinalent 6.6 9.2 36 24 30 118 118 118 119 119 119 119 119 119 119	### Solution analysis roof with in portical lights. 11 14 15 15 15 15 15 15	### Section of America (1998) Introduction analysis and with in bootstool lighter. Not detected.	vo		1	i j	\ \ /	1 6
118	118	### 1989 1989	This should be seen to	Amium	ន	8	₹	8 ;	8.5
6.6 9.2 6 11 6.70 16000 16000 21 6.53 631 630 56200 21 6.53 631 630 1460 1460 1460 1460 168 168 168 168 168 168 168 168 168 168	### Section 11 11 11 11 11 11 11	### Book 1900	### Book	omium, trivalent	8	551	& /	92	511
853 831 830 15300 21 15300 21 15300 21 15500 21	### Body & Environmyent (1988).	15300 1530	15300 1530	belt	9.6	9.5	•/ /	= }	6.9
16400 16600 16500 21 NA N	16400 16600 16500 21 653 631 630 1460 1460 1460 1460 1460 1460 1460 146	16400 1650	16400 1650	Jedd	8740	₹ 0029	~ 0000 ~	15300	2610
653 631 986 1460 1460 1460 1460 1460 1460 1460 146	## NA	Maria Mari	MA	iron	16400	18600	0000	28200	21300
197 153 218 82 82 82 82 82 82 82 82 82 82 82 82 82	The state - Ecology & Environmyent (1989).	NA	The second of th	9	S		88 :	9	By
197 153 216 82 158 82 1	197 153 216 62 168 502 R° 82 1520 R° 33 4.1 4 2 2 1520 R° 82 1520	197 153 218 628 158	197 153 218 628 628 630 638	gnesium	≨ '	≨ ;	\$	\$ 8	§ §
23 41 41 4 2 1520 R° 33 41 14 15 15 15 15 15 15 15 15 15 15 15 15 15	15 150 R° 502 R° 62 1520 R° 33 4.1 4 2 2 1520 R° 33 4.1 4.1 4 2 2 1520 R° 33 6 15 6 15 6 15 6 15 6 15 6 15 6 15 6	1	1	nganese	261	2 :	218	3 3	2
33 4,1 4,1 4, 2,2 1,1 1,4 1,5 1,5 1,5 1,5 1,5 1,5 1,5 1,5 1,5 1,5	33 4.1 4.2 2.2 2.2 2.3 4.1 1.4 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5	33 41 41 4 2 15 10 11 14 15 15 15 15 15 15 15 15 15 15 15 15 15	33 41 41 12 12 15 15 15 16 15 16 15 16 15 16 15 16 16 16 16 16 16 16 16 16 16 16 16 16	rcury	0.73	(60	80 0031	B67 B
22 22 24 46 15 15 16 25 24 46 15 1900 11900 11900	10 11 14 15 10 22 20 20 24 46 22 20 27 24 46 3310 66650 3410 11900 24 46 25 25 26 27 24 46 310 11900	10 11 14 15 15 15 15 15 15	10 11 14 15 10 22 28	34	F 3	ж Ж	י ג >		: }
22 24 48 27 24 48 48 27 24 48 48 27 24 48 24 48 24 24 48 24 24 48 24 24 24 24 24 24 24 24 24 24 24 24 24	data - Ecology & Environment (1988).	10 10 10 10 10 10 10 10	10 10 10 10 10 10 10 10	Lenium	5.5	-	• ;	1 4	1
22 24 16 23 27 24 48 3310 6650 3410 11900	data - Ecology & Environment (1988).	15 22 28 24 48 25 25 26 24 48 25 25 25 25 26 26 26 26	data - Ecology & Environment (1989). Duplicate analysis not with in bontrol lights. Spite sample recovery not with its conficul lights. Not detected.	÷	è	= -/ -	<u>*</u>	2 ◀	: :
3310 6860 3410 11900 de	Hum 3310 6860 3410 11900 at 48 20 data - Ecology & Environment (1989).	de a of data - Ecology & Environment (1989). Duplicate analysis not with in bontrol lights. Colta annote secured with the control lights.	lium 3310 6650 3410 11900 e of data - Ecology & Environment (1969). Spike sample recovery not with ith copiliol lights. Not detected	Enjine .	<i>'</i>	'/' '~	ı	· •	1
3310 6660 3410 11900 Cde	Hum 3310 6850 3410 11900 de - 3.8	de 3410 11900 de 3.8 = 3.8 e of data - Ecology & Environment (1989). Duplicate analysis not with in bontrol lights. Color semale recovery and with its control lights.	lium 3310 6850 3410 11900 de e of data - Ecology & Environment (1989). Spike sample recovery not with in bontrol lights. Not detected		SJ. 1		' 2	2 4	· X
3.8	de - Scology & Environment (1988).	of data - Ecology & Environment (1989). Duplicate analysis not with in bontrol lights. Solds connection economy and with the control lights.	Spike sample recovery not with th copilor lights. Spike sample recovery not with th copilor lights.	madium	1		\$ 5.75		64 13
	3.8 - Sology & Environment (1988).	of data - Ecology & Environment (1988). Duplicate analysis not with in bontrol lights. Colta sample recovery and with in bontrol lights.	A data - Ecology & Environment (1988). Duplicase analysis not with in bontrol lights. Spike sample recovery not with in conficil lights. Not desected.	2	0.55		2 ₹	3	3
>	nurce of data - Ecology & Environment (1988).	mos of	0 000	Cyanide		3.8	1	ŧ	:
					ongo mener.				

			Site L		
Sample Identification:	DC-L1-02	DC-L2-03	DC-13-04	00014-09	00014:10
Sample Depth:	(5-10)	(5-15)	(5-15.)	(10-20)	(10-20.)
	12/12/86	12/12/86	12/12/86	12/12/86	12/13/86
Parameter (concentrations in ppb)				<	Ò
Auminum	10697	5205	7380	1130	1378
Antimony	1	æ	1	· へ 〉	
Arsenic	* 10	ı	172	. 88	. 33
Burium	197	2 4	781	Ξ	142
Berylium	,	1	1	, ,	ı
Boron	1	1	•	, 	ı
Cadmium	1	•	\$	· >	t
Chromium, trivalent	5	15	9	1	9
Cobait	•	•	a ,	:	t
Copper	12	8	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	25	101
fron	16053	2564	668 11	1500	1446
Lead	•	901	>	* 50	• •
Magnesium	\$;	¥.	¥ ~	ş	3
Manganese	8	Į	6	9	5
Mercury	1 8	' §	00.7	1 6	' (
Catacitum	5	3	7867	3	33
		-	1	t	t
Thallism	\ \ !		1		(
Tie	<u>'</u> ,	<u>~</u>	. !	1 :	ı
unipere.	Æ	or /	9	1	ı t
Zinc	8	¥ ./	991	=	9
Cyanida	½	غ	Ź	Ź	Ž

MCA 3156895

Protected Material: Monsanto insurance Coverage Litigation


Table 4. Summary of Inorganic Compounds Detected in Sediments and Soils from Dead Creek Sector B, and Sites L and M, Sauget - Cahokia, Illinois


 				
	*****	Site M	**************************************	/
Sample Identification:	DC-SD-15	DC-SD-16	DC-SD-17	
Sample Depth:	(0-0.5')	(0-0.5')	(0-0.5')	
Sample Date:	11/5/86	11/5/86	11/5/86	\
Parameter	,0,00	,0,00	,0,00	`/
(concentrations in ppb)			/	<u> </u>
				``
Numinum	6560	2430	7510	
Antimony	••	-	-/ 🗸	/ >
Arsenic	3.6 R	12 R	16 R	- <i>[</i>
Berium	156	131	196	
Benylium	••		- \	
Boron	••	-	`	
Cadmium	1.5	11	. 8	
Chromium, trivalent	15	37 /	53	
Cobalt	7.7	7.2	5	
Copper	167 *	1270 🔨	1780	
ron	11100 ,	26000 \	14400/	
Lead	26	65 \	<i>਼</i> ੇ ਮ	
Magnesium	NA	NA \	(NA	
Manganese	100	97	\ 139	
Mercury	0.13	0.56	/ 0	
Nickel	356 R*	258 R*	√ 309 R*	
Selenium	- /) -	-	
Silver	1 ~	\	,-	
Thallium	/- ()	-	-	
Tin .	1. /6		-	
Vanadium	18	\	19	
Zinc	868	872	1010	
Cyanide	- \	/ -	-	
		/		

Source of data - Ecology & Environment (1988).


- Duplicate analysis not with in control limits.
- R Spike sample recovery not with in control limits.
- Not detected.
- NA Not analyzed. ppb Parts per billion.

MCA _156898







MCA _156899




MCA C156900






MCA -156902









PROPOSED SCHEDULE OF ACTIVITIES FOR THE SOIL BORING PROGRAM, SAUGET-CAHOKIA. ILLINOIS

FIGURE